secvest.®

FU5929

Secvest Key 2WAY wireless cylinder, O:45/I:40mm

The Secvest Key 2WAY wireless cylinder is an optional accessory for the Secvest 2WAY. It is the first cylinder lock, which automatically deactivates the alarm system when it is unlocked and activates it when it is locked. An LED on the Secvest Key 2WAY always indicates the current status of the alarm system. The Secvest Key 2WAY wireless cylinder is easy to install: The old cylinder is removed and the wireless cylinder is installed. The knob is located on the inside of the door. Then the Secvest Key 2WAY is secured using the so–called shielded screw –finished. The wireless cylinder fits in all Euro profile doors. It can be integrated in all ABUS locking systems and also in cylinder systems from other manufacturers. If the wireless cylinder is taught–into the system, the usual "unlocking of the door" suffices to disarm the alarm system. To activate the system, the button on the rotating door knob must be pressed before it is closed. You can lock the doors without pressing this button, but the system will not be activated. The wireless cylinder comes in different lengths for the outer dimension and inner dimension (from 30/30mm to 70/75mm). You can find the correct cylinder length as follows:

Product highlights:

- World's first wireless locking cylinder
- Convenient activation and deactivation of the Secvest 2WAY
- one button control
- Can be integrated into other locking systems
- Status display via LED

You determine the outer dimension by measuring the length from the center of the fastening screw to the outside of the collar (or of the fitting).

You determine the inner dimension by measuring the length from the center of the fastening screw to the inside of the collar (or of the fitting). Add an overlap of 5 mm to the inner dimension.

There are 3 keys in the delivery kit. You can order a suitable replacement key for the Secvest 2WAY wireless cylinder at any time or have a copy made at a key–making service.

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.

secvest.®

FU5929

Secvest Key 2WAY wireless cylinder, O:45/I:40mm

Technical Data	
power supply	3V lithium
Type of battery	CR2477N
Battery service life	approx. 12 months
Temperature range	–10 to +55 °C
Environmental class	2
Wireless radio	868MHz, narrow band "security band"
Output	10mW
Inner dimensions	40mm
Outer dimensions	45mm

© 2012 ABUS Security–Center GmbH & Co. KG, Errors and omissions excepted.